

Wireless Network Controller

WC-3000

Complete Control and Management of Public Access Networks

ValuePoint Networks' WC-3000 provides efficient, flexible, and complete Wi-Fi connectivity to HotSpots and other Public Access venues such as hotels, MTUs/MDUs, and a wide variety of retail locations. The Controller support wired, wireless, or hybrid networks. It is an all-in-one solution for larger locations using its built-in high powered Access Point, with 200 mWatt transmit output, and 4 dBi omni directional antennas, for a total output of 27 dBi. The Controller will automatically adjust to almost any foreseeable subscriber configuration, and adapt to support that subscriber automatically and transparently. Subscriber access can be authenticated via Local User Database or RADIUS Authentication, and printing, web browsing, and email are automatically configured and supported by the gateway as well. Pricing for the WC-3000 will dramatically lower your infrastructure costs, making previously unreachable venues affordable and increasing your Return on Investment.



Plug and Play Wireless Connectivity

Controller Adapts to Subscriber Laptop Settings

The wireless subscriber can access the Controller with no change to his/her existing IP related settings, such as IP address, subnet mask, default gateway IP address, or HTTP Proxy in his/her notebook computer. No matter what settings the subscriber has in the notebook computer, the subscriber always can access the Controller.

Corporate and ISP mail servers often will not accept E-Mail from another network. With the Wireless Controller 3000 Subscriber's outgoing SMTP server requests can be redirected to a SMTP server specified by administrator, so the subscriber can send out their email without changing the E-Mail configuration in their notebook computer.

Customized Branding

Subscriber experience can be branded for each venue

The venue owner or system integrator can customize the branding and messaging for each HotSpot. Login pages, messages, and advertising can all be configured to match the Café, Hotel, or Airport experience.

Flexible User Authentication

Secure authentication based on industry standard or Local User Database Subscriber authentication on the WC-3000 Controller can be configured for the industry standard RADIUS AAA. RADIUS allows you to control multiple sites from a single NOC, or purchase authentication services from a third party billing provider. RADIUS authentication also allows support of Wireless Roaming services such as Boingo, GRIC, or iPass.

Advanced Local Authentication

Authentication can also be controlled totally within the Network Controller 3000 using a local user database of 512 username/password accounts. Unlike the typical primitive Local Authentication feature on HotSpot Gateways, WC-3000 local accounts are richly manageable by account start and end dates and access time. And after their initial login, subscribers can be given access to the network without needing to revalidate their account.

Café Account

Customers can be given free access to the Network for a defined period, after which they would have to purchase more time to continue to browse or access the network from their laptop. This is ideal to allow free "use but don't abuse" access to draw customers into the venue.

Branded Terms of Service

The Terms of Service feature allows the Administrator to upload images and text to create a custom branded Terms of Service agreement. Users will have to agree to the terms before being granted access. It is ideal for public venues that do not want to charge for service but want to have more security than using "No Authentication".

Walled Garden and Advertising

Free Access and Promote your Partner Sites

You define a select list of web sites that can be accessed without subscriber login, in order to promote your public access venue and drive interest. This can significantly raise your awareness and help sign up new users.

The WC-3000 allows you to define a list of web sites for advertising purposes. These sites are displayed to the user on occasion to allow certain sites to be promoted. This gives your revenue sharing opportunity with your partners.



Security and Management

Highly secure and manageable

In addition to Radius-based authentication, the WC-3000 provides SSL login, and VPN pass-through.

The Wireless Controller 3000 is easy for administrators to manage through the Web-based interface. The Web-based management is client-independent and is done by securely authenticating the administrator over SSL. In addition, a sophisticated Syslog server is built-in to log events and enable automated monitoring.

XML and SOAP

Secure Management via Back End Interfaces

XML combined with SOAP allows rich, full featured, and secure control and monitoring of the Network Controller 3000. The WC-3000 SOAP interface works today with Hilton's HSIA Authentication, AuthDirect Tollbooth, DataValet, LogiSense, Thinwires, V-Link, and Wandering Wi-Fi.

High Powered 200 mW and dual 4 dBi Antennas

200mWatt output and high receive sensitivity

The Wireless Controller 3000 includes a high-power 200mW Access Point, and dual 4 dBi omni directional antennas to cover larger locations. It is fully compatible with an 802.11b or 802.11g clients, ensuring the usability with any Wi-Fi equipped device.

Networking

Broadband Internet Connection Support

The WC-3000 provides feature rich networking capabilities including DHCP Server, DHCP Client, PPPoE, DHCP Proxy, and HTTP Proxy. This means the WC-3000 can connect to any DSL, cable, T1, or other broadband service available, offering you the widest range of choices.

The WC-3000 also features four 10/100Mbps RJ-45 Fast Ethernet ports. This allows additional access points or other network devices to be supported without adding more hardware to your installation.

Technical Specifications

Wireless

- IEEE 802.11b
- Dual 4 dBi omni directional antennas
- 200mW output at SMA connector
- Range: Up to 1000 feet (300 meters) indoor

Networking

- Auto-IP supports any network configuration
- PPPoE
- IP Multicast
- SMTP Redirection
- Multiple VPN Connection Support
- Dynamic DNS
- DHCP Server, Client, and Relay
- NAT (RFC 1631)
- Transparent HTTP Proxy Server

Hardware

- 20 Concurrent Users
- 512 user local database

Security

- Secure HTML Login Page (SSL)
- Extensive System Log (Syslog) Monitoring
- IP and MAC address pass-through and blacklist
- VPN pass-through (IPSec/PPTP/L2TP)
- Web-based management
- Local or remote firmware upgrade
- Hours of service control for public venues
- LAN Device Monitoring and Management
- XML/SOAP secure management
- Customizable Firewall
- Real-time session list
- Remote management IP control
- GRE tunneling

Local Services and Branding

- Walled garden
- Standard or Customized Login, Welcome, Terms of Service, and Logout Pages
- One Time or Time-based Advertisement URLs

User Authentication and Accounting

- 'Captive Portal' Login Page Redirection
- Backup, Restore, and Export Local User Database
- Local User Database for Name/Password Logins
- Advanced Local Account Management
- ICOA TollBooth™ Authentication
- Logout Window Timer Control
- Café Account - Time-limited free access
- RADIUS client
- HiltonFamily™ HSIA Authentication
- Simple "Terms of Service" Login Option

Hardware

- 4 Switched 10/100M Fast Ethernet LAN ports
- 8 x 4 x 1 In. / 2.4 Lbs.
- 1 10/100M WAN port
- 0-55° C operating temperature

Certification and Approval

- FCC part 15 Class B
- CE Mark
- VCCI Class B
- UL

Warranty

- One year parts and labor

About ValuePoint Networks

ValuePoint is a manufacturer of Wi-Fi products for service providers, small and medium sized businesses, and the shared access market. ValuePoint's products are designed for the unique needs of Service Providers, Wireless ISPs, Billing Providers, and Venue Operators in the burgeoning mobile access space. For more information on ValuePoint's Rugged Access Points and Wireless Gateways, please visit us online.

www.valuepointnet.com